



Single Use Wet Curing Blanket

UltraCure NCF™
Disposable Wet Cure Blanket

Material Specification:

UltraCure NCF™ moisture-retaining covering by McTech Group, Inc. is a natural colored cellulose fabrics with a 3 mil white reflective impervious coating applied to one side designed to help provide protection against UV degradation. The non-staining fabric has a tensile strength meeting ASTM D- 882 and a minimum retention capacity of 6.5(g). Material shall meet or exceed ASTM C171-03, ASTM C171-97a and AASHTO M171-00, standard specifications for sheet material for curing concrete slabs or pavement.

Application:

Place wet, UltraCure NCF™ wet cure covering in widest practical width as soon as concrete has hardened sufficiently to prevent surface damage. Sides and end shall be lapped at least 3". Immediately repair any holes or tears during curing period using wet cure material and water. Cover entire surface area including edges of paving and sidewalks. Install UltraCure NCF™ moisture containing wet cure covering material as per manufacturer's written instructions. Wet surface of slab on-grade with 1/8" to 1/4" inch of water to cover entire surface area of slab, then slowly unroll the UltraCure NCF™ product onto slab using the roller squeegee applicator. No portion of this product shall be reused once it has been put into use on a slab on grade or other concrete application. Maintain UltraCure NCF™ in place on concrete for a period of not less than seven (7) days after placement. Continuous inspection for the purpose of maintaining 100 % curing blanket contact with surface to be cured is recommended.

Physical Properties: UltraCure NCF™

Property	Value	ASTM Test Method
Caliper	1.4 mm	ASTM D - 5199
Tensile	TD 4783 psi	ASTM D - 882
	MD 4900 psi	
Elongation	TD 721%	ASTM D - 882
	MD 622%	
Elmendorf	TD 1500 g	ASTM D - 1922
	MD 350 g	
Dart	300 g	ASTM D - 1709
Reflectance	> 70%	ASTM E - 1447

TD= Transverse Direction MD= Machine Direction

Technical Assistance Contact:

McTech Group, Inc.
3502 Diversified Drive
Loganville, Ga. 30052
Toll Free: 1-866-913-8363
Fax: 770-913-8307
Web: www.McTechGroup.com

The information provided herein is based upon data believed to be reliable. All testing is performed with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee, express or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use. ©2009, McTech Group, Inc. All rights reserved.